



威 佳

威佳电气，
每位工程师的专业选择！

UE-iPart

Product Introduction



使用产品前请仔细阅读本使用说明，并请妥善保管

1 产品概述

Product Description

- ▶ 优质高强度冷轧钢电镀，产品标准：GB/T 19334-2003/IEC60715；
- ▶ 颜色：三价彩锌；
- ▶ 工作温度：-40° C 持续高温至 100° C；
- ▶ 使用方法：固定于面板后即可安装电器；
- ▶ 产品特性：具美观及抗重压之功能，尺寸十分精确，耐腐蚀；
- ▶ 产品功能：多单元结构连接，实现电气元件的方便快捷安装！

- ▶ High quality and high strength cold rolled steel electroplating, product standard: GB / T 19334-2003 / iec60715;
- ▶ Color: trivalent color zinc;
- ▶ Working temperature: - 40 ° C, continuous high temperature to 100 ° C;
- ▶ Usage: after fixed on the panel, the electrical appliance can be installed;
- ▶ Product features: beautiful and anti pressure function, very accurate size, corrosion resistance;
- ▶ Product function: multi unit structure connection, realize the convenient and quick installation of electrical components!

2 产品详情

Product Details

钢材 Steel	型号 Model	短路电流强度 Short Circuit Current Intensity	材料厚度 Thickness	长度 Length
	iS 35X15X1.5/5.2X25/ST	25mm ²	1.5mm	2m
	iS 35X15X1.5/5.2X18/ST	25mm ²	1.5mm	2m
	iS 35X15X1.5/ST	25mm ²	1.5mm	2m
	iS 35X7.5X1.0/5.2X25/ST	16mm ²	1mm	2m
	iS 35X7.5X1.0/5.2X18/ST	16mm ²	1mm	2m
	iS 35X7.5X1.0/ST	16mm ²	1mm	2m

<p>铝 Aluminium</p>	<p>型号 Model</p>		<p>材料厚度 Thickness</p>	<p>长度 Length</p>
	<p>iS 35X7.5X1.2/5.2X25/AL/A PEN 联接方式时的额定电流 =125A</p>		<p>1mm</p>	<p>2m</p>
	<p>iS 35X7.5X1.2/5.2X25/AL/B PEN 联接方式时的额定电流 =125A</p>		<p>1mm</p>	<p>2m</p>
<p>铜 Copper</p>	<p>型号 Model</p>	<p>短路电流强度 Short Circuit Current Intensity</p>	<p>材料厚度 Thickness</p>	<p>长度 Length</p>
	<p>iS 35X15X1.5/CU PEN 联接方式时的额定电流 =309A</p>	<p>150mm²</p>	<p>2.3mm</p>	<p>2m</p>

无锡威佳电...

UE-iPart

Product Introduction

Vaule Plus,
Professional Choice of Each Engineer!

无锡威佳电力科技有限公司

